


# **AX-IT® PLUS**

Concentrate 1:10

# Very Aggressive No-Rinse Stripper



This fast-acting, floor finish liquifier will solve stripping difficulties caused by frequent high speed burnishing, super hard urethane fortified finishes, or excessive build-up. Utilizing evaporating liquifier technology, this product is designed to remove layers of floor finish in less time, with less effort, and no rinsing. Based on solvency to dissolve old wax and finish, rather than harsh alkalies, this stripper will not leave an alkaline residue requiring multiple rinsing. Floors are ready to recoat without neutralizing when used as directed. In many applications, the entire stripping process can be completed without the use of a floor machine and pad.

### USES

Use to remove:

# **Waxes**

- Carnauba
- Microcrystalline **Finishes**
- Acrvlic
- Copolymer
- Metal crosslinked

# Sealers

- Acrylic
- Water-based urethane
- Polymer
- Styrene
- Thermoplastics

Oligomer

NOTE: This aggressive stripper is a powerful product designed specifically for floor finish removal on resilient tile floors (vinyl and vinyl asbestos). It should not be used on wood floors or painted surfaces. Not recommended on linoleum or rubber tile floors since bleaching and softening may occur. Test first on asphalt tile in an inconspicuous area. Bleaching could occur.

#### **BENEFITS**

- Labor saving Reduces labor hours by 30 50% over conventional stripping products. Save time by quickly cutting through multiple layers of finish and save even more time by not having to rinse.
- Powerful formula Cuts through layers of old finish in minutes. Low foaming makes pickup easy whether using a wet vacuum or an automatic scrubber.
- Rinse free This stripper never requires rinsing as no alkaline residue will be left on the floor. Detail mopping of slurry trails and edges is desirable.
- Evaporation point depressants slow evaporation of stripper when using hot water, speeding up the stripping process.

# **PROPERTIES**

Color	
Flash point	None
Fragrance	Sassafras
Freeze/thaw stability	3 cycles
pH	13.5 - 14.0
pH @ 10% solution	12.8
Specific gravity	1.04



### **DIRECTIONS FOR USE**

Read the entire label before using this product. Dilute accordingly with cool to warm water. For normal stripping dilute 13 oz./gal. or 100 mL/L (1:10) of water. For aggressive stripping dilute 26 oz./gal. or 200 mL/L (1:5) of water. Apply solution liberally with mop. Allow 4 - 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a lowspeed rotary machine or automatic scrubber. Pick up solution using a wet vacuum or automatic scrubber. Allow floor to dry thoroughly. No rinsing is necessary if surface appears free of dust and residue.

# **SAFETY**

Keep out of reach of children. For institutional and commercial use.

DANGER: Corrosive. Contains Potassium Hydroxide, 2-Butoxyethanol, and Monoethanolamine. Avoid contact with skin and eyes. Wear chemical antisplash goggles, suitable gloves and boots. Harmful if swallowed. FIRST AID: If splashed on skin or in eyes, flush with large quantities of water for 15 minutes. If inhaled, get to fresh air. If swallowed, dilute with several glasses of water. Do not induce vomiting. Call a physician immediately.

# **AUTHORIZATION**

Requires no authorization by USDA prior to its use in offices and other similar nonprocessing areas.

### AVAILABLEIN

Case/4-1 Gallon (3.78 L): #15404 Pail/5 Gallon (18.9 L): #15405 Drum/55 Gallon (208 L): #15455

Authorized Betco Distributor:

Better Solutions Come From...

