

EXTREME®

Concentrate

High Power • Fast Acting • Low Odor • No-Rinse Floor Stripper



This high power, high speed floor stripper was developed to penetrate and remove multiple coats of burnished floor finish with a minimum of labor. Utilizing the latest in technology, this powerful professional stripper actually “unlocks” the chemical bonds of acrylic and urethane fortified floor finishes, releasing them from the floor surface. This fast acting, labor saving product requires little if any scrubbing and greatly reduces the time it takes to strip a floor. This powerful professional stripper has a lower pH than competitive formulas and requires no neutralizing or flood rinsing after use. Developed for use on resilient floors, this product is also suitable for use on most stone and marble floors.

USES

Use to remove:

- Waxes
- Carnauba
- Microcrystalline
- Sealers
- Acrylic

Finishes:

- Acrylic
- Copolymer
- Metal crosslinked
- Thermoplastics
- Oligomer
- Polymer
- Styrene

NOTE: This aggressive stripper is a powerful product designed specifically for floor finish removal on resilient tile floors (vinyl and vinyl asbestos.) It should not be used on wood floors or painted surfaces. Not recommended on linoleum or rubber tile floors since bleaching and softening may occur. Test first on asphalt tile in an inconspicuous area. Bleaching could occur.

BENEFITS

- Extremely Powerful - Developed to quickly strip multiple coats of burnished finish from a variety of floors.
- Labor Saving - Reduces labor by requiring a minimum of scrubbing or rinsing. Reduces labor time by up to 50% when compared to standard strippers.
- Rinse Free - Has a lower pH than competitive formulas, requires no neutralization or rinsing.
- Low odor.

PROPERTIES

Color	Green
Flash point	N/A
Fragrance	Pleasant
Freeze/thaw	N/A
pH	11.8 - 12.8
pH at dilution	11.0 - 11.4
Residue on evaporation	None
Shelf life	1 year
Specific gravity	0.993



DIRECTIONS FOR USE

Read the entire label before using this product.

1. Sweep or dust mop the floor to remove any large debris.
2. Dilute 25 oz./gal. or 200 mL/L (1:5) with cool water. Liberally apply this solution to floor surface and allow to remain for about 5 minutes. Be sure the surface stays wet with stripper solution at all times.
3. Agitate with scrubbing machine. In most cases, one pass with the scrubber will remove even the toughest finish build-ups.
4. Pick up the stripper solution with a wet vacuum, autoscrubber, or mop and bucket.
5. Damp mop with clear, cool water. Allow floor to dry thoroughly before applying finish or sealer.

NOTE: To determine the optimum use-dilution, pretest on a small area. Strip only a manageable area at one time.

SAFETY

Keep out of reach of children. For institutional and commercial use. WARNING: Contains 2-Butoxyethanol and monoethanolamine. Avoid contact with skin and eyes. Wear chemical anti-splash goggles and suitable gloves and boots. Harmful if swallowed. FIRST AID: If splashed on skin or in eyes, flush with large quantities of water. Remove contaminated clothing immediately. If inhaled get to fresh air. If swallowed, do not induce vomiting. Drink a large quantity of water. Call a physician.

AVAILABLE IN

Case/4 - 1 Gallon (3.78 L): #18404
Pail/5 Gallon (18.9 L): #18405
Drum/55 Gallon (208 L): #18455

Authorized Betco Distributor:

Better Resources. Better Results.

BETCO®